

# TPR Flexible Ducting

**Thick Walled Thermoplasticised Rubber Duct with  
Good Oil and Abrasion Resistance**

- **Appearance:** Corrugated Black Rubber
- **Application:** Flexible Ducting for fumes, air and grains.
- **Construction:** Black TPR Rubber & high carbon spring steel spiral
- **Temp Range:** -10° to 120°C
- **Flexibility:** Excellent
- **Heavy Wall:** 0.65mm to 0.70mm, 20% thicker than other brands



- ☒ **Robust HD Style**
- ☒ **Extra Thick Wall**
- ☒ **Heavy Gauge Wire**

Order Number	Nominal I.D. (mm)	Nominal I.D. (inches)	Wall Thickness (mm)	Vacuum Rating KPa @20°C	Min Bend Radius (mm)	Lengths (m)
TPR040	38	1 ½	0.6	30	30	10
TPR045	45	1 ¾	0.6	25	35	10
TPR050	51	2	0.6	20	40	10
TPR057	57	2 ¼	0.6	17	50	10
TPR065	64	2 ½	0.6	17	55	10
TPR075	76	3	0.6	17	65	10
TPR083	83	3 ¼	0.6	16.5	70	10
TPR090	89	3 ½	0.6	16	75	10
TPR100	102	4	0.6	13	85	10
TPR115	115	4 ½	0.6	12	90	10
TPR120	120	4 ¾	0.6	11	95	10
TPR125	127	5	0.6	11	105	10
TPR140	140	5 ½	0.6	9	115	10
TPR150	152	6	0.6	9	125	10
TPR160	160	6 5/16	0.6	8	135	10
TPR180	179	7	0.6	6	150	10
TPR200	203	8	0.6	5	165	10
TPR230	229	9	0.6	4	185	10
TPR250	254	10	0.6	4	210	10
TPR300	305	12	0.6	3	250	10

**Applications:** Flexible Ducting hose, for Fume and Dust extraction. Venting and Air intakes. Moderate abrasion resistance for handling of granular materials. Extreme flexibility and lightweight make this hose easier to bend, position and carry, an important asset for OHS issues.

**Comparative Advantages:** \* Thicker and more durable than other brands  
\* Packed in compressed state for easier handling and reduced damage in transit.